



Structured Cable Products

Quality Installations Deserve Quality Products

4x4 HDMI™ MATRIX SWITCHER

Part # 949



FEATURES

- Easy to use: install in seconds, no need for setting.
- Allows up to four HDMI audio/video devices to be independently switched to four HDMI monitors, HDTVs, or projectors.
- The four outputs could show the same or different source simultaneously no matter the source is HDCP or not.
- Support high definition resolutions 1080p, 1080i, 720p and other standard video formats.
- Each port supports HDMI or DVI inputs.
- With extra infrared receiver extension.
- Three switching modes: panel buttons, local IR and RS232.
- HDCP compliant.
- HDMI 1.3 version.

SPECIFICATIONS

Operating Temperature Range: -5 to +35°C (-41 to +95 °F)
Operating Humidity Range: 5 to 90 % RH (no condensation)
Input Video Signal: 0.5-1.0 volts p-p
Input DDC Signal: 5 volts p-p (TTL)
Signaling Rate: 2.25Gbit/s
Video Format Supported: DTV/HDTV:1080P/1080i/720P/576P/
480P/576i/480i

Audio Format Supported: DTS-HD Dolby trueHD
Output Video: HDMI1.2 and HDMI 1.3
Maximum Transmission Distance: <15m
(If needed, HDMI extender is optional)
Power Consumption: 12watts (Max)
Dimensions: 440mmL×202mmW×42mmH
/17.3''L×7.9''W×1.7''H
Mass (Main Unit): 2kg/4.4lb