



NOTE:
FOR REQUIRED MATERIAL SPECIFICATIONS, INSTALLATION NOTES, AND TOLERANCES SEE DRAWING B841300

ELEVATION

MAX. REACTIONS

MOMENT = 1,563 FOOT POUNDS
SHEAR = 211 POUNDS
VERTICAL = 600 POUNDS

VOLUME OF CONCRETE

SQUARE PIER = .7 CU. YDS.
ROUND PIER = .5 CU. YDS.

RI	REV. FND FOR NORMAL SOIL	2/27/96	CSR	WMN	XK
THIS DRAWING IS THE PROPERTY OF UNR-ROHN. IT IS NOT TO BE REPRODUCED, COPIED OR TRACED IN WHOLE OR IN PART WITHOUT OUR WRITTEN CONSENT.					
DRAWN BY: WDU		DATE: 9/16/87		ROHN TITLE: DRILLED PIER FOUNDATION DETAIL FOR NORMAL SOIL PER ANSI/EIA-222-E FOR BRACKETED 25 TOWER	
CHECKED BY: WRF		DATE: 9/29/87			
APP'D. ENG: XK		DATE: 2/12/88			
APP'D. SALES: AE		DATE: 2/12/88			
FILE NUMBER:					
DRAWING NUMBER: A871298R1					