

ATTENUATORS / CATV SECURITY PRODUCTS

ATTENUATORS



FAM-*
F TYPE ATTENUATOR



FAM-*HR
HIGH PERFORMANCE, HRL



FAMP-*
DC POWER PASSING
F TYPE ATTENUATOR



FAMP-*HR
DC POWER PASSING
F TYPE ATTENUATOR, HRL

SPECIFICATIONS	FAM-*	FAM-*HR	FAMP-*	FAMP-*HR
Frequency Range	5 MHz - 3 GHz	5 MHz - 3 GHz	DC - 3 GHz	DC - 3 GHz
Attenuator Values	3, 6, 8, 10, 12, 16, 20 dB	3, 6, 8, 10, 12, 16, 20 dB	3, 6, 8, 10, 12, 16, 20 dB	3, 6, 10 dB
Accuracy	± .5	± .5	± 1	± .5
Flatness	.2	.2	1.5	.6
Return Loss (1 GHz / 2 GHz / 3 GHz)	22 / 18 / 15	27 / 23 / 20	18 / 14 / 8	26 / 25 / 20
Max. Voltage / Max. Current	-	-	35VDC / 750mA	35VDC / 750mA

PPLT SERIES LOCKING TERMINATORS

This locking terminator has been specially designed to overcome problems of theft and tool breakage.



PPLT-75



PPLT-LR



PPLT-T

- Heavy Duty Zinc Body
- High Theft Resistance
- Patented Locking Mechanism (# 5,106,312)
- Unique Tool Design

GLT SERIES LOCKING TERMINATORS

- Aluminum Body
- Compatible with GTP-59
- Widely Used for Over 25 Years



GLT



GLT-LR



GLT-T

SECURITY SLEEVES



SS
HEAVY DUTY ZINC BODY



SSS
THREADED FRONT



SS-NS
NYLON BODY



ST-1
TOOL FOR SS SLEEVES