



Thread Diameter and Take Up (in)	Working Load Limit (lbs)	Dimensions(in)				Weight (lbs) Eye/Eye	Weight (lbs) Jaw/Eye	Weight (lbs) Jaw/Jaw
		A	B	C	D			
1/4 X 4	500	0.45	0.62	0.78	0.34	0.30	0.32	0.39
5/16 X 4 1/2	800	0.5	0.87	0.94	0.44	0.46	0.47	0.54
3/8 X 6	1200	0.54	0.87	1.12	0.53	0.73	0.76	0.83
1/2 X 6	2200	0.63	1.06	1.44	0.72	1.46	1.53	1.57
1/2 X 9	2200	0.55	1.06	1.44	0.72	1.71	1.76	1.95
1/2 X 12	2200	0.55	1.06	1.44	0.72	2.19	2.20	2.24
5/8 X 6	3500	0.82	1.31	1.75	0.88	2.47	2.65	2.80
5/8 X 9	3500	0.82	1.31	1.75	0.88	2.90	3.06	3.35
5/8 X 12	3500	0.82	1.31	1.75	0.88	3.48	3.78	4.00
3/4 X 6	5200	1.03	1.50	2.09	1.00	3.90	4.00	4.30
3/4 X 9	5200	1.03	1.50	2.09	1.00	4.60	4.75	4.89
3/4 X 12	5200	1.03	1.50	2.09	1.00	5.46	5.76	5.90
3/4 X 18	5200	1.03	1.50	2.09	1.00	6.97	7.00	7.52
7/8 X 6	7200	1.23	1.75	2.38	1.25	5.85	6.29	6.84
7/8 X 12	7200	1.23	1.75	2.38	1.25	7.65	8.00	8.60
7/8 X 18	7200	1.23	1.75	2.38	1.25	10.25	10.60	11.44
1 X 6	10000	1.31	2.06	3.00	1.44	8.98	9.16	9.44
1 X 12	10000	1.31	2.06	3.00	1.44	11.31	11.40	11.53
1 X 18	10000	1.31	2.06	3.00	1.44	14.00	14.75	16.10
1 X 24	10000	1.31	2.06	3.00	1.44	16.02	17.50	18.60
1 1/4 X 6	15200	1.86	2.81	3.56	1.81	15.45	16.03	16.69
1 1/4 X 12	15200	1.86	2.81	3.56	1.81	19.00	20.00	23.00
1 1/4 X 18	15200	1.86	2.81	3.56	1.81	22.50	24.18	26.60
1 1/4 X 24	15200	1.86	2.81	3.56	1.81	25.00	28.50	31.20
1 1/2 X 12	21400	2.25	2.81	4.06	2.12	27.00	31.10	35.50
1 1/2 X 18	21400	2.25	2.81	4.06	2.12	31.69	35.00	40.70
1 1/2 X 24	21400	2.25	2.81	4.06	2.12	38.20	44.20	47.60
1 3/4 X 18	28000	2.6	3.38	4.62	2.38	45.20	48.80	52.40
1 3/4 X 24	28000	2.6	3.38	4.62	2.38	58.00	60.00	64.00
2 X 24	37000	2.62	3.69	5.75	2.69	81.57	102.00	115.00
2 1/2 X 24	60000	3.06	4.44	6.50	3.12	180.00	183.00	200.00
2 3/4 X 24	75000	3.68	4.19	7.00	3.25	210.00	214.00	248.00

*Ultimate load is 5 times working load limit.