

SCP PART#: LUTRON-GREEN-P

Composite Cable

UNSH 2/C 18/7 SBC 0.008" Plenum INS Black & Red Colors,
SHLD 2/C 22/7 SBC 0.015" FFEP INS Purple & White, O/A SHIELD & 24/7
STC Drain; FOIL & Drain Facing in & O/A MYLAR & 0.025" PVC FT6 Plenum JKT

Conductor : Unsh 2/C 18/7 & SHLD 2/C 22/7 Bare Copper	
Cable & Spool Weight: 17 kgs/1000ft	Final Diameter : 0.263 inches
Insulation : Plenum	Jacket : 0.025" Plenum
Approvals : UL OR C(UL) CMP (UL) CL3P	
Print Notes :	Sequentially marked per 2FT (0 - infinity)
Standard Print :	STRUCTURED CABLE PRODUCTS - - - P/N LUTRON-GREEN-P - - - 2/C 22 AWG BC STRANDED SHIELDED W/DRAIN + 2/C 18 AWG BC STRANDED - - - E198134-SCP (UL) OR C(UL) CMP (UL) CL3P 75°C - - - CE EU ROHS EC P§ - - - ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 ROHS

75 degrees Celsius and 300V Cable Rated
Total Cable Weight : 55 kg/km
Spool Dimension: 12x12" Plywood

UNSH 2/C 18/7 Bare Copper
DC Resistance 25°C: 16.7 Ohms/1000'
Mutual Capacitance: 19.9 pF/ft
Impedance: 85 Ohms
Velocity of Prop: 60%
Inductance: 1.4 mH/km

SH. 2/C 22/7 Bare Copper
DC Resistance 25°C: 15.0 Ohms/1000'
Mutual Capacitance: 46.8 pF/ft
Shield Capacitance: 84.7 pF/ft
Velocity of Prop: 70%
Inductance: 1.3 mH/km

(All of the above values are approximated to within +/-10%)

LUTRON-GREEN-PLENUM